



**Catena calibrata DIN 766
Calibrated chain DIN 766**


Applicable normes: DIN 766/A

Acciaio Inox Stainless steel

Finitura Finishing

- Acciaio inox Aisi 316 L (1.4404) lucida
Stainless steel Aisi 316 L (1.4404) polished

Imballo Packaging



codice art. art. code	pezze da mt mts / bundle	w mm	p mm	h min. mm	H max. mm	peso Kg/mt weight Kg/mt	carico lav. Kg swl Kg
C03030CB	50/100	3	16	4,5	12	0,17	125
C03040CB	50/100	4	16	4,8	14,4	0,30	192
C03050CB	40/50/100	5	18,5	6	17	0,49	300
C03060CB	30/50/100	6	18,5	7,2	20,4	0,77	433
C03070CB	30/50/100	7	22	8,4	23,8	1,03	589
C03080CB	30/50/100	8	24	9,6	27,2	1,36	770
C03100CB	30/50/100	10	28	12	36	2,23	1200
C03130CB	25/50/100	13	36	15,6	47	3,80	2250
C03140CB	25/50/100	14	41	16,8	50	4,37	2550
C03160CB	25/50/100	16	45	19,2	58	5,55	3080

E' possibile fornire queste catene anche in grado 40 (NAUTIS 40), ideali per la nautica.

It is possible to supply all these chains also in grade 40 (NAUTIS 40), ideal for boating and marine.

Catena calibrata inox 304 disponibile solo su richiesta. Calibrated chain in stainless steel 304 available only on request.

Le catene in scatole e bobine sono esposte a pag. 55 del catalogo. Chains in boxes and reels are shown on page 55 of the catalogue.

