



**Catena calibrata
Calibrated chain**

Applicable norms: ISO 4565 / EN 818-3 / ISO 1834


Acciaio Inox Stainless steel

Grado 40

Finitura Finishing

- Acciaio inox Aisi 316 L (1.4404) lucida
Stainless steel Aisi 316 L (1.4404) polished

Imballo Packaging



codice art. art. code	pezze da mt mts / bundle	w mm	p mm	h min. mm	H max. mm	peso Kg/mt weight Kg/mt	carico lav. Kg swl Kg
C03060CB	30/50/100	6	18	7,2	20,4	0,77	500
C03070CB	30/50/100	7	21	8,4	23,8	1,03	784
C03080CB	30/50/100	8	24	9,6	27,2	1,36	1000
C03100CB/30	30/50/100	10	30	13	37	2,13	1500
C03120CB	25/50/100	12	36	14,5	41	3,04	2160
C32130CB	25/50/100	13	39	15,6	47	3,78	2501
C03140CB	25/50/100	14*	42	16,8	50	4,37	3000

Catena calibrata inox 304 disponibile solo su richiesta. Calibrated chain in stainless steel 304 available only on request.

* Catena 14p42 è in accordo alla norma NF E26-011. Chain 14p42 is according to the norm NF E26-011.

